

## MATERIAL SAFETY DATA SHEET

### CV-2943 PART A

NuSil Technology urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and fire prevention, as necessary or appropriate to the use and understanding of the data contained in this MSDS.

To promote safe handling, each customer or recipient should: (1) notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information regarding hazards or safety; (2) furnish this same information to each of its customers for the product; and (3) request its customers to notify their employees, customers and other users of the product of this information.

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

NuSil Technology 1050 Cindy Lane Carpinteria, California 93013 USA (805) 684-8780	<b>EMERGENCY TELEPHONE NUMBERS:</b> (800) 424-9300 <b>CHEMTREC</b> (805) 684-8780  <b>OUTSIDE OF THE USA</b> (703) 527-3887 <b>CHEMTREC</b>
---	--

**PRODUCT NAME:** CV-2943 Part A  
**CHEMICAL NAME:** N/A  
**CHEMICAL FAMILY:** Silicone  
**FORMULA:** Proprietary  
**MOLECULAR WEIGHT:** N/A  
**SYNONYMS:** N/A  
**CAS # :** Mixture

#### 2. HAZARDOUS INGREDIENTS

%	<u>MATERIAL</u>	<u>CAS #</u>	<u>EXPOSURE VALUE</u>	<u>CLASSIFICATION</u>
80	Aluminum oxide	01344-28-1	See Section 7	See Section 8
2	Tetra-n-propyl silicate	00682-01-9	See Section 7	See Section 8

#### 3. HAZARDS IDENTIFICATION

**EFFECTS OF SINGLE OVEREXPOSURE:**

**SWALLOWING:**

Small amounts transferred to the mouth by fingers during use, etc., should not injure. Swallowing large amounts may cause digestive discomfort.

**SKIN ABSORPTION:**

No evidence of adverse effects from available information.

**INHALATION:**

Short-term harmful health effects are not expected from vapor generated at ambient temperature.

**SKIN CONTACT:**

May cause skin irritation and reddening.

**EYE CONTACT:**

May cause irritation, experienced as stinging, excess blinking and tear production. Excess redness of the conjunctiva may occur.

**EFFECTS OF REPEATED OVEREXPOSURE:**

Repeated inhalation of aluminum oxide dust may cause lung damage. However, since the aluminum oxide in this product is compounded into the polymer matrix, it is not expected to present the same hazards as in the neat form.

**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:**

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:**

The EPA has expressed concern regarding the possible adverse health effects resulting from the inhalation of alkoxy silanes and has recommended that administrative and mechanical means be used to minimize exposures.

n-Propanol, which is generated upon exposure to water and/or moisture, has been demonstrated to be carcinogenic in lifetime exposure studies in rats when administered orally or subcutaneously.

**OTHER EFFECTS OF OVEREXPOSURE:**

None currently known.

**4. FIRST AID MEASURES**

**EMERGENCY AND FIRST AID MEASURES:**

**SWALLOWING:**

No emergency care anticipated.

**SKIN:**

No emergency care anticipated.

**INHALATION:**

No emergency care anticipated.

**EYES:**

Immediately flush eyes thoroughly with water for at least 15 minutes. Seek medical attention if discomfort persists.

**NOTES TO PHYSICIAN:**

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

**5. FIRE FIGHTING MEASURES**

**FLASH POINT** (test method(s)): > 275° C (Cleveland Open Cup)

**FLAMMABLE LIMITS IN AIR** (by volume):

LOWER: N/A                      UPPER: N/A

**EXTINGUISHING MEDIA:**

Apply alcohol-type or universal-type foams by manufacturer's recommended technique for large fires. Use water spray, carbon dioxide, dry chemical media for small fires.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Do not spray a solid stream of foam directly into a pool of hot, burning liquid as this may cause frothing, and may intensify the fire. Use self-contained breathing apparatus when fighting fire in an enclosed area.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Do not extinguish fires with water. Contact with water may generate n-Propanol, which is highly flammable. See Section 10 for further information.

## 6. ACCIDENTAL RELEASE MEASURES

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal.

WASTE DISPOSAL METHOD: Dispose of in accordance with all Federal, State, and local regulations.

## 7. HANDLING AND STORAGE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Normal precautions common to safe manufacturing practice should be followed in handling and storage.

Keep container closed, in a cool dry place. S3/S7/S8

Avoid contact with skin and eyes S24/S25

Avoid contacts with water or moisture R101

Wash thoroughly after handling.

Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### OCCUPATIONAL EXPOSURE VALUES AND SOURCE:

Aluminum oxide: 10 mg/m<sup>3</sup> - 8 hrs. TWA (Total dust) (ACGIH)  
5 mg/m<sup>3</sup> - 8 hrs. TWA (Respirable dust) (OSHA)

Tetra-n-propyl silicate: Observe values for n-Propanol, formed on exposure to water or humid air:  
200 ppm - 8 hours TWA (ACGIH, OSHA, NIOSH)  
250 ppm - STEL/CEIL(C) (skin)(ACGIH, OSHA, NIOSH)

### RESPIRATORY PROTECTION:

Use approved respirator or self-contained breathing apparatus as needed to maintain personnel exposure below established Occupational Exposure Value.

### VENTILATION:

General (mechanical) room ventilation with local ventilation as needed to maintain exposure below established Occupational Exposure Value

PROTECTIVE GLOVES: PVC-coated.

EYE PROTECTION: Use safety glasses.

OTHER PROTECTIVE EQUIPMENT: Eye bath and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES (based on typical material)

BOILING POINT: N/A

SPECIFIC GRAVITY (H<sub>2</sub>O=1): 2.5

FREEZING POINT: N/A

VAPOR PRESSURE : N/A

VAPOR DENSITY (air=1): N/A  
EVAPORATION RATE (Butyl Acetate=1): N/A  
SOLUBILITY IN WATER (By wt): Insoluble  
APPEARANCE: Gray  
ODOR: Odorless  
PHYSICAL STATE: Paste  
PERCENT VOLATILES (by wt): See Section 15

Note: The above information is not intended for use in preparing product specifications.

## 10. STABILITY AND REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY: None known.

### HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS:

Burning can produce carbon monoxide, carbon dioxide, oxides of silicon, and hydrocarbons. Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant. Acute overexposure to the products of combustion may result in irritation of the respiratory tract.

HAZARDOUS POLYMERIZATION: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### COMPONENT:

CV-2943 PART A:

Acute Oral LD <sub>50</sub> (mg/kg):	500-5000 (Rat) Inferred from ingredient hazard(s)
Acute Dermal LD <sub>50</sub> (mg/kg):	1000-2000 (Rbt.) Inferred from ingredient hazard(s)
Acute Inhalation LC <sub>50</sub> (mg/l):	2-20 (Rat) Inferred from ingredient hazard(s)
Other:	N/A.
Ames Test:	N/A.

Refer to Section 3 for further discussion of the health hazards associated with this preparation.

## 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Complete information not yet available.

CHEMICAL FATE INFORMATION: Complete information not yet available.

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all Federal, State, and local regulations.

## 14. TRANSPORT INFORMATION

I.A.T.A. HAZARD CLASSIFICATION:

None (Not Regulated)

## 15. REGULATORY INFORMATION

**STATUS ON SUBSTANCE LISTS:**

The concentrations shown are maximum or ceiling levels (weight %) to be used for calculations for regulations. Trade Secrets are indicated by "TS".

<b>C.H.I.P. REGULATIONS</b>
-----------------------------

Chemicals (Hazards Information and Packaging) Regulations 1993 requires physico-chemical and health hazard determination of all substances and preparations manufactured, transported, stored, modified, or consumed within the EEC. Components present in this product at a level which could require reporting under the statute are:

<u>MATERIAL</u>	<u>CAS NUMBER</u>	<u>UPPER BOUND CONCENTRATION</u>
n-Propanol (generated upon exposure to moisture)	00071-23-8	2 %

---

<b>FEDERAL EPA</b>
--------------------

Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification of the National Response Center of release of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQ's) in 40 CFR 302.4. Components present in this product at a level which could require reporting under the statute are:

\*\*\*\* NONE \*\*\*\*

---

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQ's) and release reporting based on Reportable Quantities (RQ's) in 40 CFR 355 (used for SARA 302, 304, 311, and 312). Components present in this product at a level which could require reporting under the statute are:

\*\*\*\* NONE \*\*\*\*

---

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This information must be included in all MSDS's that are copied and distributed for this material. Components present in this product at a level which could require reporting under this statute are:

\*\*\*\* NONE \*\*\*\*

---

**INVENTORY STATUS**

The ingredients of this product are listed on, or are exempt from listing on, the TSCA inventory.

---

**STATE-RIGHT-TO-KNOW****CALIFORNIA Proposition 65**

This product contains no levels of listed substances, which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute.

---

**MASSACHUSETTS 105 CMR 670.000 Right-To-Know, Substance List (MSL)**

Hazardous Substances and Extraordinarily Hazardous Substances on the MSL must be identified when present in products. Components present in this product at a level which could require reporting under the statute are:

<u>MATERIAL</u>	<u>CAS NUMBER</u>	<u>UPPER BOUND CONCENTRATION</u>
Aluminum oxide	01344-28-1	80 %
n-Propanol (generated upon exposure to moisture)	00071-23-8	2 %

---

**PENNSYLVANIA Right-To-Know, Hazardous Substance List**

Hazardous Substances and Special Hazardous Substances on the List must be identified when present in products.

Components present in this product at a level which could require reporting under the statute are:

<u>MATERIAL</u>	<u>CAS NUMBER</u>	<u>UPPER BOUND CONCENTRATION</u>
Aluminum oxide	01344-28-1	80 %
n-Propanol (generated upon exposure to moisture)	00071-23-8	2 %

**CALIFORNIA SCAQMD RULE 443.1 VOC'S:**

Volatile Organic Components (VOC's) = Substances with vapor pressure of  $\geq 0.5$  mm Hg at 104°C (219.2°F).

This product contains < 1 % by weight VOC's.

**OTHER REGULATORY INFORMATION:**

EPA Hazard Categories: Immediate Health Hazard.

**C.H.I.P. Regulations:**

Designation: **CV-2943 PART A**  
 Symbol: Xi



Indication of Danger: Irritant  
 Safety Phrases: S3/S7/S8/S24/S25  
 (Ref. Sect. 7) R101

**16. OTHER INFORMATION**

**HMIS FORMAT:**

Health: 1

Flammability: 1

Reactivity: 0

We believe that the information contained herein is current as of the date of this Material Safety Data Sheet, and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of NuSil Technology, it is the user's obligation to determine the conditions of safe use of the product.

-NuSil Technology Regulatory Compliance Department

Effective Date: November 7, 2002