
Polymer Systems Technology Limited

UK & Ireland Distributor



 $^{\mbox{\scriptsize \mathbb{C}}}$ 2011 - Polymer Systems Technology Limited $^{\mbox{\scriptsize \mathbb{M}}}$ Unit 2. Network 4. Cressex Business Park, Lincoln Road, High Wycombe, Bucks. HP12 3RF
Phone +44 (0) 1494 446610
Fax: +44 (0) 1494 528611
Web: http://www.siliconepolymers.co.uk

Email: sales@silicone-polymers.co.uk





Creative Partners in a Material World

NuSil Technology

1050 Cindy Lane • Carpinteria, CA 93013 805/684-8780 • 805/566-9905 Fax www.nusil.com

An ISO 9001 Certified Company

G-9040

Silicone Stir Bearing Lubricant

Product Profile

Description

- One-part, a low viscosity methyl silicone fluid
- Less than 0.5% weight loss at 150°C (302°F)

Applications

- For preventing binding and seizing of glass stirring rods and bearings under high temperature and pressure
- Use for applications that require excellent resistance to wash out and high temperatures
- Excellent for lubricating plastic surfaces and tight fitting parts
- Use to lubricate rubbers stoppers before inserting into glass tubing

Typical Properties	Result	Metric Conv.	ASTM	NT-TM
Appearance	Clear	-	D2090	002
Specific Gravity	0.97	-	D792	003
Penetration	N/A	-	DC-CTM813	022
Melting Point	N/A	-	-	-
Volatile Content	0.5 % max.	-	D2288	004
Operating Temperature Range	−40°C to 230°C	_	-	-

Warnings About Product Safety

NuSil Technology believes that the information and data contained herein are accurate and reliable. However, the user is responsible to determine the material's suitability and safety of use. NuSil Technology cannot know each application's specific requirements and hereby notifies the user that it has not tested or determined this material's suitability or safety for use in any application. The user is responsible to adequately test and determine the safety and suitability for their application and NuSil Technology makes no warranty concerning fitness for any use or purpose. NuSil Technology has completed no testing to establish safety of use in any medical application.

NuSil Technology has tested this material only to determine if the product meets the applicable

specifications. (Please contact NuSil Technology for assistance and recommendations when establishing specifications.) When considering the use of NuSil Technology products in a particular application, review the latest Material Safety Data Sheet and contact NuSil Technology with any questions about product safety information.

Do not use any chemical in a food, drug, cosmetic, or medical application or process until having determined the safety and legality of the use. The user is responsible to meet the requirements of the U.S. Food and Drug Administration (FDA) and any other regulatory agencies. Before handling any other materials mentioned in the text, obtain available product safety information and take the necessary steps to ensure safety of use.

Specifications

Do not use the typical properties shown in this technical profile as a basis for preparing specifications. Please contact NuSil Technology for assistance and recommendations in establishing particular specifications.

Patent Warning

Packaging

25 Gram

1 Pint (455 g)

1 Gallon (3.64 kg)

5 Gallon (18.2 kg)

Warranty

6 Months

NuSil Technology disclaims any expressed or implied warranty against the infringement of any patent. NuSil Technology does not warrant the use or sale of the products described herein will not infringe the claims of any United States' or other country's patents covering the product itself, its use in combination with other products or its use in the operation of any process.

Warranty Information

NuSil Technology's warranty period is 6 months from the date of shipment when stored below 40°C in original unopened containers. Unless NuSil Technology provides a specific written warranty of fitness for a particular use, NuSil Technology's sole warranty is that the product will meet NuSil Technology's then current specification. NuSil Technology specifically disclaims any other expressed or implied warranty, including warranties of merchantability and fitness for use. The exclusive remedy and NuSil Technology's sole liability for breach of warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. NuSil Technology expressly disclaims any liability for incidental or consequential damages.