

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Revision date:
30/12/2015

Date of issue:
15/08/2013

Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product Name : R-1082
Synonyms : RTV Cure Silicone Dispersion

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Improves the adhesion of addition-cured systems to various substrates. For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
ehs@nusil.com
www.nusil.com

1.4. Emergency telephone number

Emergency : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and number Maritime)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226
Acute Tox. 4 (Dermal) H312
Acute Tox. 4 (Inhalation:vapour) H332
Skin Irrit. 2 H315
Eye Dam. 1 H318
Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger
Hazardous ingredients : Xylenes (o-, m-, p- isomers), Silanetriol, methyl-, triacetate
Hazard statements (CLP) : H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H312+H332 - Harmful in contact with skin or if inhaled

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Precautionary statements (CLP) :

- H315 - Causes skin irritation
- H318 - Causes serious eye damage
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P233 - Keep container tightly closed
- P240 - Ground/bond container and receiving equipment
- P241 - Use explosion-proof electrical, ventilating, and lighting equipment
- P261 - Avoid breathing vapors, mist, spray
- P264 - Wash hands, forearms, and other exposed areas thoroughly after handling
- P271 - Use only outdoors or in a well-ventilated area
- P280 - Wear protective gloves, protective clothing, eye protection, and face protection
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
- P302+P352 - IF ON SKIN: Wash with plenty of water
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor
- P312 - Call a POISON CENTER or doctor if you feel unwell
- P321 - Specific treatment (see section 4 on this SDS)
- P331 - Do NOT induce vomiting
- P332+P313 - If skin irritation occurs: Get medical advice/attention
- P362+P364 - Take off contaminated clothing and wash it before reuse
- P370+P378 - In case of fire: Use appropriate media to extinguish
- P403+P235 - Store in a well-ventilated place. Keep cool
- P405 - Store locked up
- P501 - Dispose of contents/container in accordance with local/national regulations

2.3. Other Hazards

Other hazards not contributing to the classification : Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	65 - 70	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Asp. Tox. 1, H304

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Silanetriol, methyl-, triacetate	(CAS No) 4253-34-3 (EC no) 224-221-9	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove contaminated clothing. Rinse immediately with plenty of water (for at least 15 minutes). Obtain medical attention if irritation develops or persists. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- First-aid measures after ingestion : Seek medical attention if a large amount is swallowed. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Harmful in contact with skin. Harmful if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness and dizziness.
- Symptoms/injuries after inhalation : Harmful if inhaled.
- Symptoms/injuries after skin contact : Harmful in contact with skin. Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

SECTION 5: Firefighting measures

5.1. Extinguishing Media

- Suitable extinguishing media : Water spray or fog, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).
- Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special Hazards Arising From the Substance or Mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.
- Reactivity : Hazardous reactions will not occur under normal conditions.

5.3. Advice for firefighters

- Precautionary measures fire : Exercise caution when fighting any chemical fire.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Avoid release to the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use special care to avoid static electric charges. Do not get in eyes, on skin, or on clothing. Do not breathe gas/vapour/aerosol.

6.1.1. For non-emergency personnel

Protective equipment : Use appropriate personal protection equipment (PPE).

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to other sections

Improves the adhesion of addition-cured systems to various substrates. For professional use only.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Provide good ventilation in process area to prevent formation of vapour. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, lighting, ventilating equipment.

Storage conditions : Keep in fireproof place. Keep container tightly closed. Store in a dry, cool and well-ventilated place.

Incompatible products : Strong bases. Strong acids. Strong oxidizers.

Incompatible products : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

For professional use only.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)		
EU	IOELV TWA (mg/m ³)	221 mg/m ³ (pure)
EU	IOELV TWA (ppm)	50 ppm (pure)

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Xylenes (o-, m-, p- isomers) (1330-20-7)		
EU	IOELV STEL (mg/m ³)	442 mg/m ³ (pure)
EU	IOELV STEL (ppm)	100 ppm (pure)
Austria	MAK (mg/m ³)	221 mg/m ³ (all isomers)
Austria	MAK (ppm)	50 ppm (all isomers)
Austria	MAK Short time value (mg/m ³)	442 mg/m ³ (all isomers)
Austria	MAK Short time value (ppm)	100 ppm (all isomers)
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	442 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Bulgaria	OEL TWA (mg/m ³)	221,0 mg/m ³ (pure)
Bulgaria	OEL TWA (ppm)	50 ppm (pure)
Bulgaria	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Bulgaria	OEL STEL (ppm)	100 ppm (pure)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	221 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	442 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
Cyprus	OEL TWA (mg/m ³)	221 mg/m ³
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m ³)	442 mg/m ³
Cyprus	OEL STEL (ppm)	100 ppm
France	VLE (mg/m ³)	442 mg/m ³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m ³)	221 mg/m ³ (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	440 mg/m ³ (all isomers)
Germany	TRGS 900 Occupational exposure limit value (ppm)	100 ppm (all isomers)
Germany	TRGS 903 (BGW)	1,5 mg/l (Medium: whole blood - Time: end of shift - Parameter: Xylene (all isomers)) 2000 mg/l (Medium: urine - Time: end of shift - Parameter: Methylhippuric(tolur-)acid (all isomers))
Gibraltar	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Gibraltar	OEL TWA (ppm)	50 ppm (pure)
Gibraltar	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Gibraltar	OEL STEL (ppm)	100 ppm (pure)
Greece	OEL TWA (mg/m ³)	435 mg/m ³
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m ³)	650 mg/m ³
Greece	OEL STEL (ppm)	150 ppm

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
Italy	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Italy	OEL TWA (ppm)	50 ppm (pure)
Italy	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Italy	OEL STEL (ppm)	100 ppm (pure)
Latvia	OEL TWA (mg/m ³)	221 mg/m ³
Latvia	OEL TWA (ppm)	50 ppm
Spain	VLA-ED (mg/m ³)	221 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value)
Spain	VLA-EC (mg/m ³)	442 mg/m ³
Spain	VLA-EC (ppm)	100 ppm
Switzerland	VLE (mg/m ³)	870 mg/m ³
Switzerland	VLE (ppm)	200 ppm
Switzerland	VME (mg/m ³)	435 mg/m ³
Switzerland	VME (ppm)	100 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	210 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	442 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	220 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	441 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	200 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	109 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Estonia	OEL TWA (mg/m ³)	221 mg/m ³
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m ³)	442 mg/m ³
Estonia	OEL STEL (ppm)	100 ppm
Finland	HTP-arvo (8h) (mg/m ³)	220 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Hungary	AK-érték	221 mg/m ³
Hungary	CK-érték	442 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	221 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	442 mg/m ³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Lithuania	IPRV (mg/m ³)	200 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	450 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Luxembourg	OEL TWA (mg/m ³)	221 mg/m ³
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m ³)	442 mg/m ³
Luxembourg	OEL STEL (ppm)	100 ppm

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Xylenes (o-, m-, p- isomers) (1330-20-7)		
Malta	OEL TWA (mg/m ³)	221 mg/m ³ (pure)
Malta	OEL TWA (ppm)	50 ppm (pure)
Malta	OEL STEL (mg/m ³)	442 mg/m ³ (pure)
Malta	OEL STEL (ppm)	100 ppm (pure)
Norway	Greenseverdier (AN) (mg/m ³)	108 mg/m ³
Norway	Greenseverdier (AN) (ppm)	25 ppm
Norway	Greenseverdier (Korttidsverdi) (mg/m ³)	135 mg/m ³
Norway	Greenseverdier (Korttidsverdi) (ppm)	37,5 ppm
Poland	NDS (mg/m ³)	100 mg/m ³
Romania	OEL TWA (mg/m ³)	221 mg/m ³
Romania	OEL TWA (ppm)	50 ppm
Romania	OEL STEL (mg/m ³)	442 mg/m ³
Romania	OEL STEL (ppm)	100 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	221 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	442 mg/m ³
Slovenia	OEL TWA (mg/m ³)	221 mg/m ³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m ³)	442 mg/m ³
Slovenia	OEL STEL (ppm)	100 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	221 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	442 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Portugal	OEL TWA (mg/m ³)	221 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)
Portugal	OEL STEL (mg/m ³)	442 mg/m ³ (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapours may be released. Proper grounding procedures to avoid static electricity should be followed.

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.



Materials for protective clothing : Wear fire/ flame resistant/retardant clothing.
Hand protection : Wear chemically resistant protective gloves.
Eye protection : Chemical goggles or safety glasses.

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Skin and body protection	: Wear suitable protective clothing. Wash contaminated clothing before reuse.
Respiratory protection	: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
Environmental exposure controls	: Do not allow the product to be released into the environment.
Other information	: When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Translucent
Odour	: Sweet/Solvent
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 26,7 °C (79,9°F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative Density	: 0,92
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

VOC content	: 65 - 70 %
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical stability

Flammable liquid and vapour.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Ignition sources. Direct sunlight. Extremely high or low temperatures. Open flame. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Silicon oxides. May release flammable gases. Hydrocarbons. Smoke. Oxides of tin.

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin. Inhalation:vapour: Harmful if inhaled.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (ppm)	6247 ppm/4h (species: Sprague-Dawley)

Silanetriol, methyl-, triacetate (4253-34-3)	
LD50 oral rat	1437 - 1780 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	3,3 mg/l
EC50 Daphnia 1	3,82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2,661 (2,661 - 4,093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

12.2. Persistence and degradability

R-1082	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

R-1082	
Bioaccumulative potential	Not established.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0,6 (0,6 - 15)
Log Pow	2,77 - 3,15

Silanetriol, methyl-, triacetate (4253-34-3)	
Log Pow	0,25 KowWin

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other information : Avoid release to the environment.

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, and international regulations.
- Additional information : Handle empty containers with care because residual vapours are flammable.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1307

14.2. UN proper shipping name

Proper Shipping Name (ADR) : XYLENES (SOLUTION)
Transport document description (ADR) : UN 1307 XYLENES (SOLUTION), 3, III, (D/E)

14.3. Transport hazard class(es)

Class (ADR) : 3
Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : III


14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30
Classification code (ADR) : F1
Orange plates :



Transport category (ADR) : 3
Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
EAC code : 3YE

14.6.2. Transport by sea

MFAG-No : 130

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 65 - 70 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section	Section Header	Change	Date Changed
1.3	Details of the supplier of the safety data sheet	Modified	30/12/2015
2	Hazards identification	Added Acute Tox. 4 (Inhalation:vapour) H332. Removed DSD/DPD information.	30/12/2015
3	Composition/information on ingredients	Changed component classifications. Removed not classified components and components below cutoffs. Removed DSD/DPD information.	30/12/2015
5, 6, 7, 10	Minor wording changes to whole sections	Modified	30/12/2015
14	Transport information	Changed to UN1307	30/12/2015
15.1.1	EU-Regulations	Modified	30/12/2015

Revision date : 30/12/2015

Data sources : According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Full text of H- and EUH-statements:

Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2

R-1082

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Skin Sens. 1	Sensitisation — Skin, Category 1
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Nusil EU GHS SDS

We believe that the information contained herein is current as of the date of this Safety Data Sheet, and is offered in good faith. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of Nusil Technology, it is the user's obligation to determine the conditions of safe use of the product.



Polymer Systems Technology Limited

Silicone Sales & Services UK - Ireland - Benelux

© 2020 - **Polymer Systems Technology Limited™**

Unit 2. Network 4. Cressex Business Park,
Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: <https://www.silicone-polymers.com>

email: sales@silicone-polymers.co.uk

